

periMICA

Open Modular Edge Computer



The periMICA is the modular edge computer for your field-level IoT application, even in rough environments. It hosts virtualized applications and provides a runtime for lightweight Linux-containers. Just as you would in the cloud, the periMICA allows you to set up applications locally. So, migration of applications between the field and your IT-infrastructure becomes easy. A periMICA is the perfect tool for gathering and preprocessing data: Straight from the field-level, where sensors and actuators are networked by the Perinet Smart Components.

Key Features

- Brand labelling supported
- User-friendly web-based UI
- Fast Ethernet (100BASE-TX)
- Single Pair Ethernet (100BASE-T1)
- IoT native
 - IPv6
 - Secure by design (mTLS)
- RESTful API
- Open Source software
- Containerized Software (LXC)
- Customizable hard- & software

Hardware Customization

Processor Module

- P1** Cortex A8 Single Core, 1GB RAM, 4GB eMMC
- P2** Cortex A9 Dual Core, 2GB RAM, 16GB eMMC

Supply Module

- S1** 100BASE-TX & PoE M12, 24VDC
- S3** 100BASE-TX ix, 24VDC
100BASE-T1 M8 hybrid source

Function Module

- F2** 2 x USB-A host
- F3** rapid prototyping (breadboard)

Modular Fronts



periMICA panels from the top:
F3|S3, F3|S1, F2|S1

General Specification

Dimensions 132mm x 35mm x 86mm

Supply 24V or PoE (S1 only), compliant IEC 60950-1 / EN 60950-1 / VDE 0805-1 (SELV) or EN 50178 (PELV)

Operation Temperature -25...+75°C

Storage Temperature -25...+85°C

Relative Humidity 5...95% non-condensing

Housing Material Aluminium

Ingress Protection class IP65/67 or IP20

Mounting DIN-rail or Wall mounting Kit is available

Ordering Information

Ordering Code	Firmware Version	Description
PRN.000.025-00001	Base Fw.: 21-02	Single Core, 100Base-TX (PoE)
PRN.000.025-00002	Base Fw.: 21-02	Single Core, 100Base-TX (PoE), USB
PRN.000.025-00004	Base Fw.: 21-02	Dual Core, 100Base-TX (PoE), USB
PRN.000.025-00005	Base Fw.: 21-02	Dual Core, 100Base-TX (PoE)
PRN.000.025-00006	Base Fw.: 23-01	Single Core, 100Base-TX, 100BASE-T1
PRN.000.025-00007	Base Fw.: 23-01	Single Core, 100Base-TX, 100BASE-T1, USB
PRN.000.025-00008	Base Fw.: 23-01	Dual Core, 100Base-TX, 100BASE-T1
PRN.000.025-00009	Base Fw.: 23-01	Dual Core, 100Base-TX, 100BASE-T1, USB
PRN.000.025-00010	Base Fw.: 23-01	Single Core, 100Base-TX, 100BASE-T1, IP20
PRN.000.025-00011	Base Fw.: 23-01	Single Core, 100Base-TX, 100BASE-T1, USB, IP20
PRN.000.025-00012	Base Fw.: 23-01	Dual Core, 100Base-TX, 100BASE-T1, IP20
PRN.000.025-00013	Base Fw.: 23-01	Dual Core, 100Base-TX, 100BASE-T1, USB, IP20

further specifications are available online <https://perinet.io> or contact us for custom specifications

Support Products

Ordering Code	Product Name	Description
PRN.000.036	Wall mounting Kit	A Kit for installing the periMICA on a wall
PRN.000.037	DIN-rail mounting Kit	A Kit for installing the periMICA on a DIN-rail
PRN.000.070	IP65/67 Kit USB	Update ingress protection of a periMICA from code IP20 to code IP67 for the function module
PRN.000.071	IP65/67 Kit iX + Power	Update ingress protection of a periMICA from code IP20 to code IP67 for the supply module
33480147826010	HARTING ix Industrial® Type A to RJ45	HARTING Pre-assembled cable ix Industrial® Type A to RJ45 (S3 only)
21348400C79010	HARTING M12 Cable Assembly A-coded 12 pol st/- m/- 1,0m	System cabling, Circular connectors M12, Pre-assembled on one side, M12 A-coding, 12 cores (S1 only)